



INVESTOR IN PEOPLE


The Patent Office  
Concept House  
Cardiff Road  
Newport  
South Wales  
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.



Signed

*H. Behan*

Dated

4 March 2004

# Patents Form 1/77

Patents Act 1977  
(Rule 16)

12 AUG 2003



13AUG03 0929725-1 0000022  
P01/7700 0300-0318909.9

## Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)



The Patent Office

Cardiff Road  
Newport  
South Wales  
NP10 8QQ

1. Your reference

TJF/JG/JY/39950

2. Patent application number

(The Patent Office will fill in this part)

0318909.9

3. Full name, address and postcode of the or of each applicant (underline all surnames)

BRENDA M GADD  
36 LEWTHALL AVENUE  
GRAYS  
ESSEX  
RM1 7SAT

Patents ADP number (if you know it)

If the applicant is a corporate body, give the country/state of its incorporation

08691842001  
(see attached sheet for additional applicant)

X

4. Title of the invention

SCREENING DEVICE

5. Name of your agent (if you have one)

fj Cleveland

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

40-43 Chancery Lane  
London WC2A 1JQ

Patents ADP number (if you know it)

07368855001 ✓

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number  
(if you know it)

Date of filing  
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing  
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

- a) any applicant named in part 3 is not an inventor, or
  - b) there is an inventor who is not named as an applicant, or
  - c) any named applicant is a corporate body.
- See note (d))

NO

Patents Form 1/77

# Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form	ONE
Description	9
Claim(s)	-
Abstract	-
Drawing(s)	4 <i>alt 24</i>

*8*

10. If you are also filing any of the following, state how many against each item.

Priority documents	-
Translations of priority documents	-
Statement of inventorship and right to grant of a patent (Patents Form 7/77)	-
Request for preliminary examination and search (Patents Form 9/77)	-
Request for substantive examination (Patents Form 10/77)	-
Any other documents (please specify)	-

11.

I/We request the grant of a patent on the basis of this application.

Signature

*FJ Cleveland*  
FJ Cleveland

Date

12 August 2003

12. Name and daytime telephone number of person to contact in the United Kingdom

Mr T J Faulkner

020 7405 5875

## Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

## Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

Continuation Sheet for Patents Form No. 1/77

3. Additional applicant: MICHAEL D RICHARDSON  
36 LEWTHALL AVENUE  
GRAYS  
ESSEX  
RM1 75AT

08691859001

## Screening Device

The present invention relates to screening devices. More particularly the invention relates to changing tubes for use in changing in and out of clothing in public places, for example whilst on a beach. As will become apparent, a changing tube may be used to change in and out of clothing in a wide range of different locations, for example by the side of lakes, on camp sites etc.

Swimming in the sea or lakes is a popular pastime particularly in warm summer weather. However, it is usually necessary at some point for an individual to change in and out of his/her swimming costume, to dry himself with a towel etc by the side of the water. Different devices have been provided to allow individuals to change in comfort and privacy whilst at the beach. A well know example is a windbreaker.

15

A simple embodiment of a windbreaker comprises a plurality of poles to which are attached a sheet of material. In use the poles are driven into the ground.

The poles then support the sheet of material. The suspended sheet of material protects an individual from the wind and provides a screen behind which an

20

individual may change.

However, windbreakers have several disadvantages. They only provide a screen in a limited number of directions. It is common to set the windbreaker up so that people may sit downwind of the breaker out of the wind. In such circumstances the windbreaker does not provide privacy from people sat down  
5 wind of the breaker. Further, the use of, usually wooden, poles makes carrying the screen cumbersome. Erecting such windbreakers requires driving poles into the sand (usually by use of a mallet) and consequently it is usual to set a screen up in one location and leave it erected in that position throughout a day trip to the beach. This reduces the flexibility of use of windbreakers. The  
10 present invention aims to alleviate some of the problems associated with the prior art.

According to a first aspect of the present invention there is provided a changing tube having a stored state and a deployed state, the tube being self  
15 supporting when in a deployed state and being collapsible from the deployed state to the stored state.

The tube may comprise a coil to support walls of the changing tube. The coil may be a compression spring. When the coil is a compression spring the  
20 changing tube may comprise restriction means for restricting expansion of the compression spring when the tube is in the deployed state. The restriction

means may be adjustable to allow adjustment of the height of the changing tube when the tube is in the deployed state.

The coil may be a tension spring. In this case the changing tube comprises a support member to support the tube when the tube is in the deployed state.

The changing tube may comprise a compressible support member in at least a portion of a wall of the tube.

10 The changing tube may be open at both ends. The changing tube may comprise a removable base portion.

The changing tube may comprise means for securing the tube to the ground.

The means for securing the tube to the ground may comprise spikes arranged for placement in the ground.

The tube may be of circular cross section. Where the changing tube has a circular cross section the tube is particularly easy to change in. The circular section allows equal room in every direction for an individual changing in the centre of the tube. An individual is therefore less likely to knock against the sides of the tube whilst changing.

The changing tube may be of square cross section. In the case where the changing tube is of square cross section the changing tube is particularly convenient to store. In its collapsed state a square changing tube may be conveniently stored in boxes, on shelves etc.

5

The changing tube may be of polygonal cross section. The polygon may be a regular polygon. Alternatively the polygon may be an irregular polygon.

When in the collapsed state the changing tube may be useable as a buoyancy aid.

10

Throughout this specification the word "comprise", or variations such as "comprises" or "comprising", will be understood to imply the inclusion of a stated element, integer or step, or group of elements, integers or steps, but not exclusion of any other element, integer or step, or group of elements, integers or steps.

15

A changing tube which embodies this invention is described now by way of example only, with reference to the accompanying drawings, of which:

20

Figure 1 shows a circular changing tube;



Figures 2a and 2b is a part section through the wall of the changing tube showing different ways in which material may be attached to a coil of the changing tube shown in figure 1;

- 5 Figure 3 shows a removable base portion for use with the changing tube shown in figure 1;

Figure 4 shows the changing tube of figure 1 in a stored state;

- 10 Figure 5 shows a square changing tube.

Figure 1 shows a changing tube 1 of generally circular cross-section in its deployed state. The changing tube comprises two circular hoops 11 located at either end of the changing tube 1 and interconnected by a wall 15 of opaque  
15 material. The hoops 11 are made of low density plastics material. The changing tube 1 further comprises a coil 13 disposed between the two hoops 11. The ends of the coil 13 are attached to the hoops 11.

The coil 13 is an aluminium coil. However, in alternative embodiments the coil  
20 may be made of plastics material or another metal. The coil may be a conventional compression spring. Alternatively the coil may be a coiled hollow

tube sealed at either end.

When the changing tube 1 is in the deployed state, the coil 13 is at its natural length or near to its natural length. The spring 13 may be compressed by  
5 bringing the two hoops 11 together and releasably securing the hoops 11 together. When the two hoops 13 are adjacent to each other, the changing tube is in its stored state.

The wall 15 is made up of an opaque material, in particular the wall 15 is  
10 made up of nylon material. Figure 2A shows a part section of the arrangement of the wall 15. The wall 15 comprises an outer wall 12 and an inner wall 21. The inner wall 21 is made of the same material as the outer wall 15. The section shown in Figure 2A is from the right hand side of the changing tube 1 as shown in Figure 1. The inner wall 21 and the outer wall 12 are attached  
15 either side of the coil 13.

Figure 2B shows an alternative embodiment in which the wall 15 of the changing tube has only a single outer wall 12 located on the outside of the circular coil 13.

20

Figure 1 also shows a pair of adjustment straps 17 located between the pair of

hoops 11. Each adjustment strap 17 is attached to both hoops 11 and is of adjustable length. When the changing tube 1 is in the deployed state as shown in Figure 1 the adjustment strap 17 acts to restrict the expansion of the coil 13. Adjustment of the length of the straps 17 therefore allows adjustment of the height of the changing tube 1.

Figure 3 shows a removable base portion 3 for use with the changing tube 1. The removable base portion 3 has a base hoop 31 over which base material 33 is stretched. The removable base portion 3 has four spikes 35. The removable base portion further has attachment means (not shown) in order to attach the removable base portion to a changing tube 1.

In use, the removable base portion 3 is placed on a desired location on the ground and pressed downwards in order to drive the spikes 35 into the ground. A changing tube 1 in its stored state, with the coil 13 compressed, is then placed over the removable base portion 3 and attached to the removable base portion using the attachment means. A user then stands on the removable base portion 3 and deploys the changing tube 1 by releasing securing means 41 (shown in Figure 4). When the user has finished using the changing tube he may return the changing tube to its stored state by pulling the upper hoop 11 towards the ground. In this manner the coil 13 is compressed. When the upper

hoop 11 has been moved down to the lower hoop 11 the two hoops are secured together using the securing means 41. Figure 4 shows a changing tube in its stored state held in this stored state by the securing means 41.

- 5 When in the stored state, the changing tube 1 may be used as a buoyancy aid. The buoyancy of the changing tube 1 is provided by the low density plastic hoops 11 which cause the changing tube to float on water.

In alternatives, buoyancy may be provided by sealed coiled tubing 13.

- 10 Alternatively the inner and outer walls (15, 21) maybe airtight and the space between the walls, containing the spring 13, sealed to form an airtight compartment. Air trapped between the inner wall 21 and the outer wall 15 may provide buoyancy to the tube 1. The buoyancy is provided in a similar manner to arm bands and the walls may be made of similar material. In this case the  
15 air trapped in between the walls would not be sufficient to support the walls when the changing tube 1 is in the deployed state.

- Figure 5 shows an alternative changing tube of square cross-section. The design of this changing tube is in many respects similar to the changing tube described  
20 with respect to Figure 1. Therefore only differences between the two changing tubes will be described. The square changing tube has four sides and it is

therefore difficult to construct a coil of square section for use in such a changing tube. The changing tube in Figure 5 therefore has a wall spring 51 located in a pair of opposing sides of the changing tube 5. Only one wall spring 51 is shown in Figure 5. In the other sides are provided connecting bars which add structure to the walls. The wall spring and connecting bars together form a concertina like structure. The wall spring 51 is made up of a "zig-zagging" aluminium member attached to both square hoops 11 of the changing tube 5. As will be apparent to the person skilled in the art, in alternatives the "zig-zagging member" may be made of other materials.

10

When the changing tube 1 is deployed, the outer wall 12 may be seen by people outside the changing tube 1. It may, therefore, be desirable to use the outer wall 12 for advertising purposes. It may be that in some circumstances it would be desirable to give away changing tubes 1 to people for no charge in order to obtain advertising space on, for example, beaches.

15

17/4




Fig. 1

2/4




Fig. 2b




Fig. 2a

3/4




Fig. 3




Fig. 4



4/4




Fig. 5

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☒ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**